

ReSound Nexia™

CROS Transmitter



Model	CX177-DWC
Device Configurations	
Battery size	Rechargeable Lithium-Ion
Tube Options	Thin Tube and Plastic Hook
Control Options	Push button
IP Classification	IP68
Battery Lifetime (CROS/BiCROS fitting)	16 (typ) hours
Audiological Features	
Soft switching	•
Adaptive Autoscope	•
Fixed Directionality	•
Omni	•
Noise Reduction	Paired hearing aid options
CROS balance control	•
Connectivity Features	
Wireless accessory and direct streaming	Paired hearing aid options
Wireless fitting with NoahLink Wireless	•



Technical data	Desktop Charger
Dimensions	82,0 mm x 36,0 mm x 45,3 mm / 3.2" x 1.4" x 1.8"
Weight	82 grams / 2.9 oz
Power Supply	USB power supply, 5 V
Charging form factor (CFF)	70
Charging time for Hearing Instrument	< 35 °C (95 °F): 3 hours, depending on initial state of the battery
Wireless frequency between Hearing Instrument and Charger	2.4 GHz and 333 kHz
ESD tolerance	According to IEC 61000-4-2 Electrostatic discharge immunity test standard
Operating & Charging temperature	+ 5 °C (41 °F) to + 35 °C (95 °F) at a relative humidity range of 15% to 90%, non-condensing
Storage temperature for charger and Hearing Instrument	– 25 °C (-13 °F) to + 5 °C (41 °F), + 5 °C (41 °F) to + 35 °C (95 °F) at a relative humidity up to 90%, non-condensing, > 35 °C (95 °F) to 60 °C (140 °F) at a water vapour pressure up to 50 hPa



© 2024 GN Hearing A/S. All rights reserved. ReSound is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

402801011US CA VA-24.05-Rev.A

Manufacturer according to FDA:

Hearing aids
GN ReSound North America
8001 E Bloomington Freeway
Bloomington, MN 55420
USA
1-800-248-4327
pro.resound.com

ReSound Government Services
8001 E Bloomington Freeway
Bloomington, MN 55420
USA
1-800-392-9932
gs.resound.com

Manufacturer according to Health Canada:

Hearing aids
ReSound Canada
2 East Beaver Creek Road, Building 3
Richmond Hill, ON L4B 2N3
Canada
1-888-737-6863
resound.com

Manufacturer according to Health Canada:

Hearing aid charger
GN Hearing A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark







Technical Specifications

		CX177-DWC (Closed)		
		IEC 60118-0: 1983_ AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	46	45	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	67 56	60 53	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	135 126	128 122	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.4 1.0 0.8	0.3 0.7 0.6	%
Telecoil sensitivity (1 mA/m input)	Max.	98	91	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	110	105	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	87	83	
Equivalent input noise, w/o Noise reduction		25	20	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	10	10	dB SPL
Frequency range		<200 - 7960	<200 - 6240	Hz
Battery Lifetime (Battery type Rechargeable)*		30 (max) 24 (typ)	30 (max) 24 (typ)	Hours

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

Patents pending.

All specifications are subject to change without notice.



Technical Specifications

		CX177-DWC (Open)		
		IEC 60118-0: 1983_ AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	41	40	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	62 52	53 47	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	131 121	127 116	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.2 0.2 0.9	0.1 0.1 0.7	%
Telecoil sensitivity (1 mA/m input)	Max.	94	85	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	105	100	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	83	78	
Equivalent input noise, w/o Noise reduction		25	22	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	9	9	dB SPL
Frequency range		<200 - >8000	<200 - 6990	Hz
Battery Lifetime (Battery type Rechargeable)*		30 (max) 24 (typ)	30 (max) 24 (typ)	Hours

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

Patents pending.

All specifications are subject to change without notice.

